














intercarpet

SISAL FINE



TECHNICAL PRODUCT DATA
TECHNISCHE PRODUKT DATEN
TECHNISCHE PRODUCT GEGEVENS

SISAL FINE

Type of manufacture	Herstellingsart	Productie methode	: Woven / Gewebt / Geweven	
Gauge	Teilung	Deling	: Reed 23 / Riet 23 / Riet 23	
Width	Breite	Breedte	: 400 cm / 500 cm	
Type of surface	Oberseitengestaltung	Poolaanzicht	: Loop pile / Schlingenpol / Lussenpool	
Pile material	Nutzschicht	Poolmateriaal	: 100% Sisal	
Warp / Weft	Kette / Schuss	Ketting / Inslag	: Jute / Jute	
Secondary backing	Zweitücken	Rug	: PP fleece / PP vlies / PP vlies	
Pile weight	Polgewicht	Poolgewicht	: 700 g/m ²	ISO 8543
Total weight	Gesamtgewicht	Totaal gewicht	: 2.220 g/m ²	ISO 8543
Pileheight	Polhöhe	Poolhoogte	: 2.2 mm	ISO 1766
Total thickness	Gesamttärke	Totaal dikte	: 6.5 mm	ISO 1765
Number of tufts or loops	Noppenzahl	Noppenaantal	: 34.664 /m ²	ISO 1763
Use classification Eichnungsbereich Gebruiksclassificatie		23 Heavy domestic use 33 Heavy commercial use	 	EN 1307
Suitability for use on stairs Treppeneignung Geschiktheid voor trappen		Intensive use		EN 1963 Test B
Castor chair suitability Stuhlrolleneignung Geschiktheid voor zwenkwielen		Not suitable		EN 985 Test A
Antistatic behaviour Elektrostatische Ladung Electrostatisch gedrag		-0.2 kV at 25 %RH		ISO 6356
Thermal resistance Thermische Widerstand Thermische weerstand		0.13 m ² K/W	 TOG value 1,3	ISO 8302
Burning behaviour Brandverhalten Brandgedrag		Class Efl		ISO 11925-2 ISO 9239-1
Colourfastness to light Lichtechtheit Lichtechtheid		≥ 4		ISO 105 B02
Impact sound insulation Trittschalldämmung Contactgeluidsisolatie		Δ Lw ≥ 10 dB		EN 1307 Annex D
Luxury rating Komfort klasse Comfortklasse		Class LC1		EN 1307
Others Sonstige Overige		Class 4		EN 14041:2004 DOP: 1036-124945



Prodis ID



QR Code Prodis

